

Gulf Stream[®] *Swimming Pool Heat Pumps*

PERFORMANCE



EFFICIENCY



10 YEARS PARTS / 2 YEARS LABOR

HE-2 SERIES
SEE COMPLETE WARRANTY FOR DETAILS



WWW.GULFSTREAMHEATPUMP.COM

Gulf Stream

Swimming Pool Heat Pumps



PERFORMANCE AND EFFICIENCY:

4-Sided Evaporator Coil

Super-sized for maximum efficiency
Higher Performance in all weather
Engineered for a smaller footprint

2" Full Flow Titanium Heat Exchanger

Pipe size does not reduce once inside the unit
Maximum water flow design for higher efficiency
Lifetime titanium warranty against corrosion

Ultra-Quiet Design

Quiet scroll compressor
Commercial grade fan motor designed for quiet operation
Only 56db while in operation

Chill Buster(Heat/Cool) Option

Works In Colder Temps Or Cools The Pool

INTELLIGENT CONTROL:

(Additional wiring may be required)

GPS Affordable Spa Automation

Isolates the spa, energizes the pump & switches thermostats
Plug-ins for 2 actuators
Wireless options available

Solarwise Solar Heating Controller

Solar pool automation for hybrid pool heating control
Prioritizes solar pool heating for maximum efficiency
Actuator Plug-in & roof sensor connections

Compatible with all external Automation

Simple connection and programming
Seamless integration with all major brands of automation

Even Heat

Maintains the perfect temperature 24-hours a day

ADVANCED ASSEMBLY AND TESTING

Helium Leak Testing

100-times more accurate than the competition
Ensures optimized performance in every unit

Mass Flow Charging

The most accurate way to ensure proper refrigerant charging
Computerized accuracy to 1/100th of an ounce

Rust Proof ABS Cabinet

Strong ABS cabinet designed for harsh climates
UV inhibitors added for lifetime durability
Avoid the metal-cabinet regret

Comprehensive Final Run Test

Computerized quality control testing cannot be bypassed
Every-component in every-unit tested every-time
A "Perfect" unit every time for the ultimate peace of mind

UNIT SPEC	HE-90	HE-110	HE-125	HE-150
BTU/COP				
AHRI HIGH TEST POINT(80/80/80)	90,000/6.3	110,000/6.2	117,000/6.3	136,000/6.0
LOW TEST POINT (50/63/80)	56,000/4.0	66,000/4.1	74,000/4.1	85,000/4.0
MIN AMPS / MAX BREAKER	36/40	37/40	37/50	37/50
WEIGHT	213 LBS	215 LBS	237 LBS	239 LBS
(SHIPPING)	(241 LBS)	(243 LBS)	(265 LBS)	(267 LBS)
DIMENSIONS	31 X 31 X 38	31 X 31 X 38	31 X 31 X 42	31 X 31 X 42
(SHIPPING)	(33 X 31 X 43)	(33 X 31 X 43)	(33 X 31 X 47)	(33 X 31 X 47)



WWW.GULFSTREAMHEATPUMP.COM

